



## Mobil Super Moto Scooter 10W30

Mobil Passenger-Vehicle-Lube , India

High Performance Four-Stroke Scooter Engine Oil

### Product description

Mobil Super Moto™ Scooter 10W-30 is a high performance four-stroke scooter engine oils primarily intended for general use in all types of driving.

### Features and benefits

Mobil Super Moto™ Scooter 10W-30 combines highly refined, quality base oils with an advanced additive system to provide excellent wear, cleanliness, and corrosion protection. Mobil Super Moto™ Scooter 10W-30 is especially formulated for scooters to shield critical engine parts.

Features	Advantages and Potential Benefits
Excellent wear protection	Helps extend engine life
Thermal and oxidation stability	Helps keep engines clean for smoother operation
Good corrosion protection	Protects critical engine components

### Specifications and Approvals

<b>MOBIL SUPER MOTO SCOOTER 10W-30 meets or exceeds the requirements of:</b>
API SL
JASO MB

### Properties and Specifications

<b>MOBIL SUPER MOTO SCOOTER 10W-30</b>	
Grade	SAE 10W30
Kinematic Viscosity @ 40 C, MM <sup>2</sup> /S, ASTM D445	70.9
Kinematic Viscosity @ 100 C, MM <sup>2</sup> /S, ASTM D445	10.57
Viscosity Index, ASTM D2270	136
Ash, Sulfated, MASS%, ASTM D874	1.065
Pour Point, °C, ASTM D97	-42
Flash Point, Cleveland Open Cup, °C, ASTM D92	226
Density @ 15 C, G/ML, ASTM D1298	0.8695

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise

09-2019

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,  
Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved