



## Mobil Delvac™ CNG/LNG 15W-40

Mobil Commercial-Vehicle-Lube , Mexico

High Performance Heavy Duty Engine Oil for Spark Ignited CNG and LNG Fueled Trucks and Buses

### Product Description

Mobil Delvac™ CNG/LNG 15W-40 is a high performance heavy duty engine oil formulated specifically for spark ignited CNG and LNG fueled truck and bus engines. It provides excellent performance in the challenging operating environments presented by CNG (Compressed Natural Gas) and LNG (Liquefied Natural Gas) and offers extended drain interval capability.

### Features and Benefits

| Features  | Advantages and Potential Benefits                                      |
|---|--|
| Thermal Stability and Oxidation/Nitration Control | Extended Drain Interval Capability                                     |
| Advanced Wear Protection                          | Helps Towards Long Engine Life   |
| Effective Detergency/Dispersancy                  | Engine Cleanliness   |
| Optimized Ash Level                               | Helps Protect Against Excessive Valve Recession and Spark Plug Fouling |
| Shear Stability                                   | Engine Durability  |

### Applications

Mobil Delvac CNG/LNG 15W-40 is a high performance heavy duty engine oil formulated specifically for spark ignited CNG and LNG fueled truck and bus engines.

- Spark ignited CNG/LNG fueled stoichiometric and lean-burn engines
- Extended Drain Interval Capability
- Compatible with Exhaust Gas Recirculation (EGR) Systems, Three Way Catalysts, and other emissions reduction systems

### Specifications and Approvals

| This product has the following builder approvals: |
|---|
| Detroit Fluids Specification 93K216               |

| This product is recommended for use in applications requiring: |
|--|
| CUMMINS CES 20085  |

| This product meets or exceeds the requirements of: |
|--|
| ISUZU CNG Engine Oil                               |

## Properties and Specifications

| Property   |            |
|--|------------|
| Grade  | SAE 15W-40 |
| Ash, Sulfated, mass%, ASTM D874                            | 0.9        |
| Density @ 15 C, g/cm <sup>3</sup> , ASTM D4052             | 0.871      |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 215        |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 15.3       |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 114        |
| Pour Point, °C, ASTM D97                                   | -27        |
| Total Base Number, mgKOH/g, ASTM D2896                     | 6.4        |
| Viscosity Index, ASTM D2270                                | 140        |

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2020

ExxonMobil Mexico, S.A. de C.V.

Poniente 146 No. 760 Col. Industrial Vallejo

C.P. 02300 Mexico, D.F

(01 52) 55 5-333-9602 (01 52) 1-800-90-739-00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil Esso XTO  
2012 12 1

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved