



Mobil Delvac 1300 Mongrades

Mobil Commercial-Vehicle-Lube , Mexico

High Performance Diesel Engine Oils

Product Description

Mobil Delvac 1310, 1320, 1330, 1340, and 1350 are high performance monograde diesel engine oils formulated from advanced technology base oils and a balanced additive system. They are specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off-highway conditions. Mobil Delvac 1300 monogrades are used in a wide range of applications where a monograde lubricant is recommended.

Features and Benefits

Features	Advantages and Potential Benefits
Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Prolonged engine life Less wear Excellent protection against ring sticking
Extended TBN reserve	Long-term deposit/wear control Controls formation of acids when using higher sulfur fuels

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment
- On highway light and heavy duty trucking
- Off highway industries including: construction, mining, quarrying, and agriculture
- Hydraulic system and wet breaks in mobile equipment where a SAE 20 diesel engine oil is required (Delvac 1320)

Specifications and Approvals

Mobil Delvac 1300 Monogrades are recommended by ExxonMobil for use in applications requiring:	Mobil Delvac 1310	Mobil Delvac 1320	Mobil Delvac 1330	Mobil Delvac 1340	Mobil Delvac 1350
API CF	X	X	X	X	X
API SF	X	X	X	X	X
Merces Benz 227.0		X			

Typical Properties

Mobil Delvac 1300 Monogrades	Mobil Delvac 1310	Mobil Delvac 1320	Mobil Delvac 1330	Mobil Delvac 1340	Mobil Delvac 1350
SAE Grade	10	20	30	40	50
Viscosity, ASTM D 445					

Mobil Delvac 1300 Monogrades	Mobil Delvac 1310	Mobil Delvac 1320	Mobil Delvac 1330	Mobil Delvac 1340	Mobil Delvac 1350
cSt @ 40°C	38.1	61	106	136	232
cSt @ 100°C	6.3	8.4	11.8	14.6	19.9
Viscosity Index, ASTM D 2270	114	108	99	99	99
Sulfated Ash, wt%, ASTM D 874	0.7	1.1	1.1	1.1	1.1
Total Base #, mg KOH/g, ASTM D 2896	6.9	10	10	10	10
Pour Point, °C, ASTM D 97	-36	-21	-21	-30	-18
Flash Point, °C, ASTM D 92	226	232	256	254	260
Density @ 15°C kg/l, ASTM D 4052	0.880	0.887	0.893	0.897	0.902

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Delvac are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

03-2020

ExxonMobil Mexico, S.A. de C.V.

Poniente 146 No. 760 Col. Industrial Vallejo

C.P. 02300 Mexico, D.F

(01 52) 55 5-333-9602 (01 52) 1-800-90-739-00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved