



Mobil Super Moto 4T 20W-50

Mobil Passenger-Vehicle-Lube , Mexico

High Performance Four-Stroke Motorcycle Engine Oil

Product Description

Mobil Super Moto 4T 20W-50 is a high performance conventional four-stroke motorcycle engine oil primarily intended for general use in many types of four-stroke motorcycles and engines.

Features and Benefits

Mobil Super Moto 4T 20W-50 combines highly refined, quality mineral oils and an advanced additive system to provide good engine cleanliness, good wear protection and corrosion protection. Key features and benefits include:

Features	Advantages and Potential Benefits
Good wear protection	Helps extend engine life
Thermal and oxidation stability	Helps keep engines clean for smoother operation
Good corrosion protection	Protects critical engine components

Specifications and Approvals

Mobil Super Moto 4T meets or exceeds the requirements of:	20W-50
JASO	MA

Mobil Super Moto 4T is recommended by ExxonMobil for use in applications requiring:	20W-50
API	SG / CC

Typical Properties

Mobil Super Moto 4T	20W-50
SAE Grade	20W-50
Viscosity, ASTM D445	
cSt @ 40°C	137.9
cSt @ 100°C	17.1
Sulfated Ash, wt%, ASTM D874	0.93
Pour Point, °C, ASTM D97	-27
Flash Point, °C, ASTM D93	212
Density @15.6°C g/ml, ASTM D4052	0.89

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Super Moto 4T are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

03-2020

ExxonMobil Mexico, S.A. de C.V.

Poniente 146 No. 760 Col. Industrial Vallejo

C.P. 02300 Mexico, D.F


(01 52) 55 5-333-9602 (01 52) 1-800-90-739-00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved