



Mobil Super 3000 X1 FORMULA FE 5W-30

Mobil Passenger-Vehicle-Lube , Russia

Premium Full Synthetic Passenger Vehicle Motor Oil

Product Description

Mobil Super™ 3000 X1 Formula FE 5W-30 is a full synthetic motor oil that provides long engine life for many types & ages of vehicles with enhanced protection over a wide temperature range.

Features and Benefits

Mobil Super 3000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 3000 X1 Formula FE 5W-30 provides:

- Enhanced high temperature protection
- Enhanced cold start-up performance
- Enhanced engine cleanliness and sludge prevention
- Enhanced wear protection
- Helps in achieving fuel economy (as per ACEA A5/B5)

Applications

Mobil Super 3000 products are formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. ExxonMobil recommends Mobil Super 3000 X1 Formula FE 5W-30 if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress. Mobil Super 3000 X1 Formula FE 5W-30 can be used in a variety of gasoline and diesel automobiles, light trucks and vans designed for use of a low viscosity (HTHS) motor oil.

Mobil Super 3000 X1 Formula FE 5W-30 is intended primarily to meet the requirements of Ford but is also suitable for use in other vehicles where the viscosity and quality claims are appropriate.

Mobil Super 3000 X1 Formula FE 5W-30 can be used in all engines requiring WSS-M2C913-D and can still be used wherever WSS-M2C913-C is recommended.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
Ford WSS-M2C913-D
STJLR.03.5003

This product is recommended for use in applications requiring:
API CF

This product meets or exceeds the requirements of:

API SL

API SN Engine Test Requirements

Ford WSS-M2C913-C

ACEA A5/B5

Properties and Specifications

Property	
Grade	SAE 5W-30
Ash, Sulfated, mass%, ASTM D874	0.8
Density @ 15 C, g/ml, ASTM D4052	0.85
Flash Point, °C, ASTM D92	192
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	9.8
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	53
Phosphorus, mass%, ASTM D4951	0.05
Pour Point, °C, ASTM D97	-39

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

Mobil Oil Lubricants LLC : 123242, Moscow, Novinsky boulevard, 31, Russia

+ 7 (095) 232 22 23

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.ru/ru-ru/contact-us-technical>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved